

Overview	
Wood species	European Oak
Design	Plank
Grade	Rustic
Profile	Tongue & Groove (to all sides)
Edge Detail	4 side micro beveled
Construction	Oak veneer + 7 layer Birch plywood base (moisure resistant - EN636-1)
Wear Layer	3mm
Application Guide	Floors & walls

Finish	
Finish	Light brushed & UV lacquered (5% gloss) diara - 7 coat process (99-121 g/m ²)
Surface Texture	Lightly brushed
Handover Guidance	Fully finished & ready to use

Guarantee	
Guarantee	15 years domestic wear warranty

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR

Dimensions	
Width	180mm
Thickness	12.5mm
Length	2400mm (25% nested plank per box)
Tolerance	Top Layer: +/- .2mm Total Thickness: +/- .1mm Width: +/- .2mm Length: +/- .5mm Assembling Gap Average: ≤.2mm for every 1000mm Lipping Av: ≤.2mm
Pack size	3.024m ²
Pack weight	25.5kg

Environmental Certification	
Certification	EN 14342 / EUTR Compliant
FSC	No
Structural floor	No
Underfloor heating	Yes - Please see usage guidelines

Sub-floors	
Concrete	Dry, flat
Plywood	Yes
Screed	Dry, flat

Technical Information	
Moisture content	7% (+/-2)
Slip rating	R9
EN 14342 emissions	Yes
Humidity requirements	Between (40% to 60%)
Origin of Oak	European
Formaldehyde emission	E1 Emission

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR