



SANDERS & FINK

CUMBRIAN

LIGHT SMOKED AND OILED / UKFS0003

Overview	
Wood species	European Oak
Design	Herringbone
Grade	BCD Rustic
Profile	Single tongue & 3 side groove
Edge Detail	4 side micro beveled
Construction	Oak veneer + 11mm thick Eucalyptus plywood with Poplar backing
Wear Layer	4mm
Application Guide	Floors

Finish	
Finish	Woca Hardwax Oil 1505
Surface Texture	Light smoked
Handover Guidance	Fully finished & ready to use
Floor Care	Re apply 1-2 coats of Woca Hardwax Oil 1505 after installation

Guarantee	
Guarantee	15 years domestic wear warranty

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR

Dimensions	
Width	70mm
Thickness	15(4)mm
Length	280mm
Tolerance	Top Layer: +/-2mm Total Thickness: +/-2mm Width: +/-2mm Length: +/-3mm Assembling Gap Average: ≤.3mm, Max ≤.4mm Lipping Av: ≤.25mm Max ≤.3mm
Pack size	0.588m ²
Pack weight	8kg

Environmental Certification	
Certification	EN 14342 / EUTR Compliant
FSC	No
Structural floor	No
Underfloor heating	Yes - Please see usage guidelines

Sub-floors	
Concrete	Dry, flat
Plywood	Yes
Screed	Dry, flat

Technical Information	
Moisture content	8-10% fair & Average moisture content
Slip rating	CEN/TS 15676
EN 14342 emissions	Yes
Humidity requirements	Between (40% to 60%)
Origin of Oak	European
Formaldehyde emission	E1 Emission

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR