

Life  
flooring

# SEASONS

SPRING / CHLK0030

| Overview            |                                                                                                                    |
|---------------------|--------------------------------------------------------------------------------------------------------------------|
| Description         | Laminate Flooring (Direct Pressure, melamine impregnated decorative paper onto High Density Fibreboard (HDF) core) |
| Design              | Herringbone                                                                                                        |
| Profile             | Docloc glueless locking system (must be laid as floating floor)                                                    |
| Dimensions          |                                                                                                                    |
| Width               | 100mm                                                                                                              |
| Thickness           | 12.3mm                                                                                                             |
| Length              | 600mm                                                                                                              |
| Surface Properties  |                                                                                                                    |
| Slip resistance     | EN13893 (AC4)                                                                                                      |
| Resistance to Fire  | EN13501-1 (D <sub>fl</sub> s1)                                                                                     |
| Chemical resistance | EN13442 (Category 5)                                                                                               |
| Classifications     |                                                                                                                    |
| 24 hour swelling    | EN 622-5 (<17%)                                                                                                    |
| Bending strength    | EN 622-5 (23 N/mm <sup>2</sup> )                                                                                   |
| Moisture content    | EN 622-1 (4-11%)                                                                                                   |
| Formaldehyde        | EN 622-1 (Class E1)                                                                                                |
| Internal bond       | EN 622-5 (1 N/mm <sup>2</sup> )                                                                                    |
| Pack Details        |                                                                                                                    |
| Pack Size           | 1.8m <sup>2</sup>                                                                                                  |
| Pallets             | Made of solid wood, fumigated                                                                                      |

## FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL [ENQUIRIES@UKFLOORSUPPLIES.CO.UK](mailto:ENQUIRIES@UKFLOORSUPPLIES.CO.UK) OR VISIT [UKFLOORSUPPLIES.CO.UK](http://UKFLOORSUPPLIES.CO.UK)

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR