

Overview	
Wood species	European Oak
Design	Herringbone
Grade	Country (ABC)
Profile	Cross edge – Optilock system, transverse lock insert - HDF
Edge Detail	4 side micro beveled
Construction	Oak surface layer, pine middle and bottom layer
Wear Layer	2.5mm
Application Guide	Floors & walls

Finish	
Finish	5 layers of acrylic matt lacquer. UV hardened (3 layers of primer lacquer, 2 layers of UV hardened surface ceramic lacquer)
Surface Texture	Brushed & UV Matt Lacquer, Stained
Handover Guidance	Fully finished & ready to use

Warranty	
Warranty	15 Years Domestic Wear Warranty

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR

**Dimensions**

Width	110mm
Thickness	14mm
Length	660mm
Tolerance	Thickness: $\leq 2\text{mm}$ Width: $\pm 0.2\text{mm}$ Length: $\pm 0.1\%$
Pack size	0.5m ²
Pack weight	5.66kg

Environmental Certification

Certification	EN 14342 / EUTR Compliant
FSC	No
Structural floor	No
Underfloor heating	Yes - Please see usage guidelines

Sub-floors

Concrete	Dry, flat
Plywood	Yes
Screed	Dry, flat

Technical Information

Moisture content	7% ($\pm 2\%$)
EN 14342 emissions	Yes
Humidity requirements	Between (40% to 60%)
Origin of Oak	European
Formaldehyde emission	E1 Emission

FOR MORE INFORMATIONCALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR