

SANDERS & FINK

ARTISTS

DALI / TAMA0134

Overview	
Wood species	European Oak
Design	Herringbone
Grade	ABCD Rustic
Profile	Tongue & Groove (Left & Right)
Edge Detail	4 side micro beveled
Construction	Oak veneer + 14mm thick Eucalyptus Plywood with Poplar backing
Wear Layer	4mm
Application Guide	Floors & Walls

Finish	
Finish	Brushed & UV Matt Lacquer (Treffert)
Surface Texture	Brushed
Handover Guidance	Fully finished & ready to use

Guarantee	
Guarantee	15 years domestic wear warranty

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR

Dimensions	
Width	120mm
Thickness	18(4)mm
Length	600mm
Tolerance	Top Layer: +/-2mm Total Thickness: +/-2mm Width: +/-2mm Length: +/-3mm Assembling Gap Average: ≤.3mm, Max ≤.4mm Lipping Av: ≤.25mm Max ≤.3mm
Pack size	0.864m ²
Pack weight	10.2kg

Environmental Certification	
Certification	EN 14342 / EUTR Compliant
FSC	No
Structural floor	No
Underfloor heating	Yes - Please see usage guidelines

Sub-floors	
Concrete	Dry, flat
Plywood	Yes
Screed	Dry, flat

Technical Information	
Moisture content	8-10% fair & Average moisture content
Slip rating	CEN/TS 15676
EN 14342 emissions	Yes
Humidity requirements	Between (40% to 60%)
Origin of Oak	European
Formaldehyde emission	E1 Emission

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR