

SANDERS &amp; FINK

## ARTISTS

PICASSO / TAMA0128

| Overview          |                                                                |
|-------------------|----------------------------------------------------------------|
| Wood species      | European Oak                                                   |
| Design            | Herringbone                                                    |
| Grade             | ABCD Rustic                                                    |
| Profile           | Tongue & Groove (Left & Right)                                 |
| Edge Detail       | 4 side micro beveled                                           |
| Construction      | Oak veneer + 14mm thick Eucalyptus Plywood with Poplar backing |
| Wear Layer        | 4mm                                                            |
| Application Guide | Floors & Walls                                                 |

| Finish            |                                      |
|-------------------|--------------------------------------|
| Finish            | Brushed & UV Matt Lacquer (Treffert) |
| Surface Texture   | Brushed                              |
| Handover Guidance | Fully finished & ready to use        |

| Guarantee |                                 |
|-----------|---------------------------------|
| Guarantee | 15 years domestic wear warranty |

## FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL [ENQUIRIES@UKFLOORSUPPLIES.CO.UK](mailto:ENQUIRIES@UKFLOORSUPPLIES.CO.UK) OR VISIT [UKFLOORSUPPLIES.CO.UK](http://UKFLOORSUPPLIES.CO.UK)

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR

| Dimensions  |                                                                                                                                                                     |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Width       | 120mm                                                                                                                                                               |
| Thickness   | 18(4)mm                                                                                                                                                             |
| Length      | 600mm                                                                                                                                                               |
| Tolerance   | Top Layer: +/- .2mm<br>Total Thickness: +/- .2mm<br>Width: +/- .2mm<br>Length: +/- .3mm<br>Assembling Gap Average: ≤.3mm, Max ≤.4mm<br>Lipping Av: ≤.25mm Max ≤.3mm |
| Pack size   | 0.864m <sup>2</sup>                                                                                                                                                 |
| Pack weight | 10.2kg                                                                                                                                                              |

| Environmental Certification |                                   |
|-----------------------------|-----------------------------------|
| Certification               | EN 14342 / EUTR Compliant         |
| FSC                         | No                                |
| Structural floor            | No                                |
| Underfloor heating          | Yes - Please see usage guidelines |

| Sub-floors |           |
|------------|-----------|
| Concrete   | Dry, flat |
| Plywood    | Yes       |
| Screed     | Dry, flat |

| Technical Information |                                       |
|-----------------------|---------------------------------------|
| Moisture content      | 8-10% fair & Average moisture content |
| Slip rating           | CEN/TS 15676                          |
| EN 14342 emissions    | Yes                                   |
| Humidity requirements | Between (40% to 60%)                  |
| Origin of Oak         | European                              |
| Formaldehyde emission | E1 Emission                           |

## FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL [ENQUIRIES@UKFLOORSUPPLIES.CO.UK](mailto:ENQUIRIES@UKFLOORSUPPLIES.CO.UK) OR VISIT [UKFLOORSUPPLIES.CO.UK](http://UKFLOORSUPPLIES.CO.UK)

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR