

SANDERS & FINK

ARTISTS

REMBRANDT / TAMA0137

Overview	
Wood species	European Oak
Design	Plank
Grade	BCD Rustic
Profile	Tongue & Groove (to all sides)
Edge Detail	4 side micro beveled
Construction	Oak veneer + 14mm thick Eucalyptus plywood with Poplar backing
Wear Layer	4mm
Application Guide	Floors & walls

Finish	
Finish	Brushed & UV Matt Lacquer (Treffert)
Surface Texture	Brushed, distressed, hand scraped, rounded edges
Handover Guidance	Fully finished & ready to use

Guarantee	
Guarantee	15 years domestic wear warranty

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR

Dimensions	
Width	190mm
Thickness	18(4)mm
Length	1900mm (1 layer in 4, nested 600mm - 1300mm)
Tolerance	Top Layer: +/-2mm Total Thickness: +/-2mm Width: +/-4mm Length: +/-1mm Assembling Gap Average: <=.3mm Max <=.4mm Lipping Av: <=.25mm Max <=.3mm
Pack size	2.166m ²
Pack weight	25.4kg

Environmental Certification	
Certification	EN 14342 / EUTR Compliant
FSC	No
Structural floor	No
Underfloor heating	Yes - Please see usage guidelines

Sub-floors	
Concrete	Dry, flat
Plywood	Yes
Screed	Dry, flat

Technical Information	
Moisture content	8-10% fair & Average moisture content
Slip rating	CEN/TS 15676
EN 14342 emissions	Yes
Humidity requirements	Between (40% to 60%)
Origin of Oak	European
Formaldehyde emission	E1 Emission

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR