



# STORY

AUSTIN OAK / CLEN0088

## Overview

|                    |                                                                                                                            |
|--------------------|----------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b> | Laminate Flooring (Direct Pressure, melamine impregnated decorative paper onto Classenboard High Density Fibreboard (HDF)) |
| <b>Design</b>      | Plank                                                                                                                      |
| <b>Profile</b>     | Megaloc glueless Locking System (must be laid as floating floor)                                                           |

## Dimensions

|                  |        |
|------------------|--------|
| <b>Width</b>     | 192mm  |
| <b>Thickness</b> | 12mm   |
| <b>Length</b>    | 1285mm |

## General requirements

|                                    |                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Geometrical characteristics</b> | EN 13329<br>Width: $\pm 0.1\text{mm}$<br>Length: $\pm 0.5\text{mm}$                                                    |
| <b>Thickness</b>                   | EN13329 ( $\varnothing \leq 0.5\text{mm}$ )                                                                            |
| <b>Squareness</b>                  | EN 13329 ( $\leq 0.20\text{mm}$ )                                                                                      |
| <b>Straightness</b>                | EN 13329 ( $\leq 0.30\text{mm/m}$ )                                                                                    |
| <b>Flatness of elements</b>        | EN13329<br>Width: concave $\leq 0.15\%$ & convex $\leq 0.20\%$<br>Length: concave $\leq 0.50\%$ & convex $\leq 1.00\%$ |
| <b>Openings</b>                    | EN 13329 ( $\varnothing \leq 0.15\text{mm}$ max. $\leq 0.20\text{mm}$ )                                                |
| <b>Height difference</b>           | EN 13329 ( $\varnothing \leq 0.10\text{mm}$ max. $\leq 0.15\text{mm}$ )                                                |
| <b>Residual indentation</b>        | EN ISO 24343-1 ( $\leq 0.05\text{mm}$ )                                                                                |
| <b>Light fastness</b>              | EN ISO 4892-2 (grey scale level $\geq 4$ )                                                                             |

## FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL [ENQUIRIES@UKFLOORSUPPLIES.CO.UK](mailto:ENQUIRIES@UKFLOORSUPPLIES.CO.UK) OR VISIT [UKFLOORSUPPLIES.CO.UK](http://UKFLOORSUPPLIES.CO.UK)

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR



# STORY

AUSTIN OAK / CLEN0088

## Essential characteristics

|                         |                                                       |
|-------------------------|-------------------------------------------------------|
| Slip resistance         | EN 13893 (DS)                                         |
| Reaction to Fire        | EN 13501-1 (C <sub>fi</sub> s1)                       |
| Thermal resistance      | EN 12667 (R <sub>s</sub> ≤ 0.09 (m <sup>2</sup> K)/W) |
| Formaldehyde            | EN 16516 (Class E1)                                   |
| Formaldehyde emission   | ASTM D6007 (US EPA TSCA Title VI / CARB P 2)          |
| VOC emission            | Decret no 2011-321 (A+)                               |
| Electrostatic behaviour | EN 1815 (≤ 2kV)                                       |
| Thermal conductivity    | EN 12667 (≥ 0.75 W/mK)                                |

## Classifications

|                             |                                                                         |
|-----------------------------|-------------------------------------------------------------------------|
| Thickness swelling          | EN 24336 (≤ 15%)                                                        |
| Locking strength            | ISO 24334 (F <sub>10.2</sub> ≥ 1.0 kN/m & F <sub>s0.2</sub> ≥ 2.0 kN/m) |
| Wear resistance             | EN 13329 (IP ≥ 6000 cycles (AC5))                                       |
| Impact resistance           | EN 17368 (small-diameter ball ≥ 75mm & large-diameter ball ≥ 1000mm)    |
| Resistance to staining      | EN 438-2, 5 (group 1&2), 4 (group 3)                                    |
| Castor chair resistance     | EN 425 (no damage with type W after 25 000 cycles)                      |
| Movement of a furniture leg | EN ISO 16581 (no damage with type O)                                    |
| Surface soundness           | EN 13329 (≥ 1.25 N/mm <sup>2</sup> )                                    |

## Pack Details

|               |                                |
|---------------|--------------------------------|
| Pack Size     | (6 pieces) 1.480m <sup>2</sup> |
| Pack Weight   | 16 kg                          |
| Pallet Volume | 52 packs per pallet            |

## FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL [ENQUIRIES@UKFLOORSUPPLIES.CO.UK](mailto:ENQUIRIES@UKFLOORSUPPLIES.CO.UK) OR VISIT [UKFLOORSUPPLIES.CO.UK](http://UKFLOORSUPPLIES.CO.UK)

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR