

Life
flooring

SEASONS

SPRING EQUINOX / CHLK0038

Overview	
Description	Laminate Flooring (Direct Pressure, melamine impregnated decorative paper onto High Density Fibreboard (HDF) core)
Design	Herringbone
Profile	Docloc glueless locking system (must be laid as floating floor)
Dimensions	
Width	100mm
Thickness	12.3mm
Length	600mm
Surface Properties	
Slip resistance	EN13893 (AC4)
Resistance to Fire	EN13501-1 (D _{fl} s1)
Chemical resistance	EN13442 (Category 5)
Classifications	
24 hour swelling	EN 622-5 (<17%)
Bending strength	EN 622-5 (23 N/mm ²)
Moisture content	EN 622-1 (4-11%)
Formaldehyde	EN 622-1 (Class E1)
Internal bond	EN 622-5 (1 N/mm ²)
Pack Details	
Pack Size	1.8m ²
Pallets	Made of solid wood, fumigated

FOR MORE INFORMATION

CALL 0113 831 3324 OR EMAIL ENQUIRIES@UKFLOORSUPPLIES.CO.UK OR VISIT UKFLOORSUPPLIES.CO.UK

UK Floor Supplies Ltd. Unit 2, Orion Way, Leeds, LS9 0AR